



LIFT ASSIST CHOKE VALVE SLING



FEATURES

- Specifically designed for use in the safe manual handling of chocks and BOP choke valves.
- Allows safe handling and movement of valves, reducing possible hand and finger injuries.
- Reduces the need for bending when lifting to assist in safe manual handling procedure.
- Provides protection against accidental damage to valves & threads through controlled lifting method during assembly.
- Fully supports Hands Free/Hands Off Working Policy.

Rating	50kg WLL
Minimum Breaking Load	500kg
Factor of Safety:	In excess 10:1
Webbing Belt Strap	25mm simplex polyester webbing
Certification:	CE Marked, Safe Use Instruction Sheet
Product Code:	OHS-C100

NOTE: Lift Assist products are designed for manual handling purposes ONLY and must NEVER be used as part of any mechanical rigging or lift operations.

LIFT ASSIST DOUBLE HANDLE



FEATURES

- Designed for single or two person operation to allow safe manual lifting operations.
- Allows safe handling and movement of pup joints, chocks, IBOP valves and fishing tools as well as pipe, tubing sections and other general deck cargo lifting requirements, reducing possible hand and finger injuries.
- Reduces the need for bending when lifting to assist in safe manual handling procedure.
- Extra lengths to allow double wrapping of tubular
- Fully supports Hands Free/Hands Off Working Policy.

Rating	100kg WLL
Minimum Breaking Load	1000kg
Factor of Safety:	In excess 10:1
Webbing Belt Strap	50mm simplex x 1500mm long as standard
Certification:	CE Marked, Safe Use Instruction Sheet
Product Code:	OHS – D100

NOTE: Lift Assist products are designed for manual handling purposes ONLY and must NEVER be used as part of any mechanical rigging or lift operations.

LIFT ASSIST SINGLE HANDLE



FEATURES

- Designed for one person operation or can be ideally used in pairs for more complex manual lifting operations.
- Allows safe handling and movement of pup joints, chocks, IBOP valves and fishing tools as well as other general deck cargo lifting requirements, reducing possible hand and finger injuries.
- Reduces the need for bending when lifting to assist in safe manual handling procedure.
- Fully supports Hands Free/Hands Off Working Policy.

Rating	75kg WLL
Minimum Breaking Load	750kg
Factor of Safety:	In excess 10:1
Webbing Belt Strap	50mm simplex x 900mm long as standard
Certification:	CE Marked, Safe Use Instruction Sheet
Product Code:	OHS – S100

NOTE: Lift Assist products are designed for manual handling purposes ONLY and must NEVER be used as part of any mechanical rigging or lift operations.