



NOTES:

- FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.
- COOLING OIL (SUMP OR FLOW THRU) RECOMMENDATION: MOBIL DTE 24, CITGO A/W 32 OR EQUIVALENT
- DIMENSIONS MAY VARY BETWEEN UNITS AND ARE TO BE USED FOR REFERENCE PURPOSES ONLY
- LINEING REPAIR KIT P/N 12-501-004
- BEARING REPAIR KIT P/N 12-501-006
- O-RING REPAIR KIT P/N 12-501-002
- SPRING REPAIR KIT P/N 12-501-008

SPECIFICATIONS:

TYPE:	WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
TORQUE RATING:	WET 6,500 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES.
RELEASE PRESSURE:	210 PSI INITIAL, 290 PSI FULL
FLOW THRU CAPACITY:	1.0 - 7.0 GPM
MAXIMUM OPERATING PRESSURE:	3,000 PSI
MAXIMUM CASE PRESSURE:	15 PSI
SUMP OIL VOLUME:	HORIZONTAL SHAFT - 4 FL OZ VERTICAL SHAFT - CONTACT FACTORY
MAXIMUM SPEED:	3,900 RPM
LINEING MATERIAL:	SINTERED BRONZE
APPROXIMATE WEIGHT:	40 LB

INCH  
[MILLIMETER]

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.	MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.
--	---

<div>MICO®</div> <div>North Mankato, Minnesota USA</div>				
SCALE 0.500	TITLE 3C-141498-C24Z MULTIPLE DISC BRAKE			
	APVD PROD ENGRG PJS 2015-10-22	SIZE B	DRAWING NUMBER 13-547-048	REV H
			CUSTOMER COPY	2 3