

QTM5

FLOW RESTRICTOR VALVE


SERIES 10




MODULAR VERSION ISO 4401-05

p max 350 bar
Q max 120 l/min

MOUNTING INTERFACE




OPERATING PRINCIPLE



PERFORMANCES (measured with mineral oil of viscosity 36cSt at 50°C)

Maximum operating pressure	bar	350
Maximum flow rate	l/min	120
Cracking pressure	bar	0,5
Ambient temperature range	°C	-20 / +60
Fluid temperature range	°C	-20 / +80
Fluid viscosity range	cSt	10 ÷ 400
Recommended viscosity	cSt	25
Fluid contamination degree	According to ISO 4406:1999 class 20/18/15	
Mass: QTM5-SA, -SB, -RSA, -RSB QTM5-D, -RD	kg	2,3 2,5


HYDRAULIC SYMBOLS



1 - IDENTIFICATION CODE

<div>Q T M 5 - / 10 /</div>									
Flow restrictor valve								S = adjustment screw (standard) K1 = adjustment knob	
Modular version									
ISO 4401-05 size						Seals: N=Seals in NBR for mineral oils (standard) V= Seals in FPM for special fluids			
Versions for meter-out: D = control on lines A and B SA = control on line A SB = control on line B			Versions for meter-in: RD = control on lines A and B RSA = control on line A RSB = control on line B			Series No. (the overall and mounting dimensions remain unchanged from 10 to 19)			

2 - CHARACTERISTIC CURVES (values obtained with viscosity of 36 cSt at 50°C)



3 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4. For these fluids, use NBR seals (code N). For fluids HFDR type (phosphate esters) use FPM seals (code V). For the use of other kinds of fluid such as HFA, HFB, HFC, please consult our technical department. Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics. The fluid must be preserved in its physical and chemical characteristics.

4 - OVERALL AND MOUNTING DIMENSIONS

