

# AirXroad/4P

11n WiFi access point, Ethernet bridge, repeater & MESH point for automotive & heavy duty applications



- All-in-one : AP/client/repeater/Mesh/router
- WiFi 802.11a/b/g/n (MIMO 2T2R), radio data rate up to 300 Mbps, 2.4/5 GHz
- Easy and secure configuration: web browser (HTTPS), SNMPV3, WaveManager
- Operating System : WaveOS
- DC power supply input (+9VDC to +48VDC) & PoE 802.3af
- Multichannel fast roaming (in client mode)
- Shock & vibration proof rugged aluminium enclosure IP66 seal rating
- E-marking (ECE R10 certification for integration in onboard vehicles)



## Introduction

AirXroad/4P is a compact rugged enclosure equipment, ideally designed for applications in road transportation, depots, warehouses, agriculture, manufacturing floors, docks, distribution centers, shipyards and lumberyards... it can be mounted in trucks, city buses, forklifts, trailers, tractors or cranes or in any rotating machinery, for material handling, real-time information transmission, and inventory management.

The device relies on the multi-streams MIMO technology that contributes to an expanded coverage, higher data throughput and increased radio link reliability.

It fulfills severe requirements in terms of operating environment: from -20°C to +60°C, shock and vibration proof, protection against dust and water projections (IP66).

AirXroad is E-marked ECE R10 (EMC standard for electronic equipment installed aboard vehicle), and can thus be installed in full safety aboard of all on-road equipment.

## Technical characteristics overview

<b>Ethernet interface</b>	1-port Fast Ethernet 10/100 Base TX auto-sensing, auto MDI/MDIX cross-over, 4 pins M12 connector
<b>WiFi Interface</b>	1 radio IEEE 802.11a/b/g/n, MIMO 2T2R, 2.4 / 5 GHz
<b>WiFi radio data rate</b>	802.11a: 6, 9, 12, 18, 24, 36, 48 et 54 Mbps 802.11b/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 et 54 Mbps 802.11n: MCS0-7, 2 streams (6.5 to 300 Mbps)
<b>Operating frequencies</b>	ISM : 2.4-2.483 GHz (up to 14 channels) UNII : 5.15-5.25 GHz (up to 4 channels) UNII-2 : 5.25-5.35 GHz (up to 4 channels) UNII-2 ext : 5.470-5.725 GHz (up to 11 channels) UNII-3 : 5.725-5.825 GHz (up to 4 channels) Supports DFS and TPC
<b>RF Output power</b>	2,4 GHz : 23,5 dBm (aggregate) / 5 GHz : 21 dBm (aggregate)
<b>RF Sensitivity</b>	Receiver : -92 dBm for 802.11 b/g/n and -96 dBm for 802.11a/n
<b>Antennas connectors</b>	2 RP-SMA male connectors
<b>WiFi modes</b>	Access point, client, MESH (IEEE 802.11s), infrastructure, AD-HOC, fast roaming (less than 30 ms), WMM QoS
<b>Administration</b>	http, https, SNMP agent (V1, V2C, V3), ACKSYS WaveManager & WaveViewer administration softwares
<b>Security</b>	Firewall, DoS, https, MAC filtering, WPA2/WPA3, IEEE 802.1X/RADIUS authentication, WEP, tunnels L2 (GRE), VPN (OpenVPN), SNMP V3, Wireless Intrusions Detection System (WIDS)
<b>Ethernet networking</b>	Frames filtering, bridging, repeater, STP/RSTP, VLAN, DHCP (server & client), DNS
<b>Ethernet routing</b>	Relay Multicast (PIM), IP redundancy (VRRP), static routes, NAT router, router
<b>LEDs Signaling</b>	Radio : status - activity - DFS detection   Ethernet : link 10/100 - activity   Power - Diagnostic
<b>Power supply</b>	+9VDC to +48VDC M12 connector 4-pole A-coded & PoE 802.3af (15,4W) mode A/endspan compatible
<b>Consumption</b>	Maximum average : 5.8 W   Recommended power supply : 7 W
<b>Mechanical specifications</b>	Dimensions : 115 mm x 64 mm x 34 mm. Weight : 319 g
<b>IP rating</b>	IP66
<b>Environmental conditions</b>	Operating temperature: -20°C to +60°C, storage : -40°C à +85°C, relative humidity: 0% to 99% (non-condensing)
<b>Standards and certifications</b>	CE (RED)      Safety : EN 62368-1:2014+A11, EN62311 EMC : EN301-489-1, EN301-489-17 Radio : EN 300 328 2.1.1 (2.4 GHz), EN 301 893 2.1.1 (5 GHz, DFS)
	FCC   IC      Radio : FCC ID Z9W-RMB   Radio: IC ID 114688A RMB
	E-marking      ECE R10
	Environnement      Shocks & vibrations : EN 61373 (CAT 1 CLASS B)   Climatic : EN60068-2 [-1, -2, -30]
<b>Warranty</b>	5 years

## Ordering references

AirXroad /4P      WiFi Access Point, Ethernet Bridge, Repeater and MESH point (IEEE 802.11n a/b/g) for automotive applications, power input from +9VDC to +48VDC plus POE, shipped without cables or antennas

### Accessoires optionnels

WLg-M12U-ETH-2M      ULTRA-LOCK waterproof 4-point M12 to RJ45, Ethernet cable, 2 meters  
WLg-M12U-ETH-5M      ULTRA-LOCK waterproof 4-point M12 to RJ45, Ethernet cable, 5 meters  
WLg-M12U-ETH-10M      ULTRA-LOCK waterproof 4-point M12 to RJ45, Ethernet cable, 10 meters

WLg-M12U-PWR-2M      Power supply cable ULTRA-LOCK M12 4 pts, 2 meters  
WLg-M12U-PWR-5M      Power supply cable ULTRA-LOCK M12 4 pts, 5 meters  
WLg-M12U-PWR-10M      Power supply cable ULTRA-LOCK M12 4 pts, 10 meters

WL-ANT-2458/2-ORPS      Dual band (2.4 / 5 GHz) 2 dBi omni-directional RP-SMA antenna

AXR-SET/4P      Connecting set includes:  
- 1 x WLg-M12U-PWR-2M  
- 1 x WLg-M12U-ETH-2M  
- 2 x WL-ANT-2458/2-ORPS

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.

ACKSYS\_AirXroad\_4P\_US\_Rev A0\_11/08/21