

RESCUE HOOK, STATIC DISCHARGE STICK

Salisbury Insulated Rescue Hook is an invaluable tool for any workplace used to withdraw an injured worker out of a hazardous area. Confined spaces, in vaults, or just near electrical cabinets and switch gear are some of the places where this tool is a must. Featuring a foam filled, fiberglass reinforced handle for superior electrical insulation and a coated heat treated body hook with an 18" opening. The stick is available in the standard lengths of 6 and 8-foot lengths. Other lengths are available as a special order. Contact us with your requirements. Handle meets the requirements of ASTM F711.

The Static Discharge Stick is designed to safely remove the static charge after de-energizing. This tool is pre-assembled and includes a copper "U" hook, 3'6" closed cell foam filled tubular fiberglass stick and 6' of copper grounding cable attached to a Salisbury 1814 bronze flat jaw serrated grade 3 clamp. Also available in a 1' length stick.



WARNING:

Discharge sticks are not grounding tools as described by OSHA 1910.269 and carry no fault duty rating.



Insulated Rescue Hook



Static Discharge Stick
w/ Universal Attachment



Static Discharge Stick

Cat. No.	Dimensions		Weight ea.	
	in.	mm	lbs.	kgs
INSULATED RESCUE HOOK				
24400	Rescue Hook 3' (0.9 m) length		3.4	(1.5)
24401	Rescue Hook 6' (1.8 m) length		4.5	(2)
24403	Rescue Hook 8' (2.4 m) length		5.5	(2.5)
STATIC DISCHARGE STICK				
20817	Static Discharge Stick OAL 3'8" (1.08m) length		8	(3.6)
22629	Static Discharge Stick w/ Universal Attachment 1' (0.3m) length		.38	(0.17)