



2/2-Way Solenoid Valve Type PGV Series 100 Pressure Operated by External Medium - Double-Sided Isolating


Price group	53	Function "B" normally open (without control pressure)	low noise and impact-free closing, for neutral, gaseous and fluids	Amb. temp. $T_{min} -20\text{ }^{\circ}\text{C}$, $T_{max} +60\text{ }^{\circ}\text{C}$ Med.-Temp. $T_{min} -10\text{ }^{\circ}\text{C}$, $T_{max} +90\text{ }^{\circ}\text{C}$	Brass				
Version	Control pressure [bar]	DN	Kv-value water [m³/h]	G	PN	Sealing material	Type	Order number	Price
2/2-way valve pressure operated, isolating double-sided by external medium Permitted operating pressure 0.2 to 16 bar 	≥ operating pressure max. 16	15	5.6	G 1/2	16	NBR	PGV-131-B76-1/2BP	614201	o. r.
		15	5.6	G 1/2	16	EPDM	PGV-131-B76-1/2PP	614203	o. r.
		15	5.6	G 1/2	16	FKM	PGV-131-B76-1/2FP	614205	o. r.
		20	7.6	G 3/4	16	NBR	PGV-131-B76-3/4BP	614211	o. r.
		20	7.6	G 3/4	16	EPDM	PGV-131-B76-3/4PP	614213	o. r.
		20	7.6	G 3/4	16	FKM	PGV-131-B76-3/4FP	614215	o. r.
		25	16.8	G 1	16	NBR	PGV-131-B76-1BP	614221	o. r.
		25	16.8	G 1	16	EPDM	PGV-131-B76-1PP	614223	o. r.
		25	16.8	G 1	16	FKM	PGV-131-B76-1FP	614225	o. r.
		32	21	G 1 1/4	16	NBR	PGV-131-B76-5/4BP	614231	o. r.
		32	21	G 1 1/4	16	EPDM	PGV-131-B76-5/4PP	614233	o. r.
		32	21	G 1 1/4	16	FKM	PGV-131-B76-5/4FP	614235	o. r.
		40	29.5	G 1 1/2	16	NBR	PGV-131-B76-6/4BP	614241	o. r.
		40	29.5	G 1 1/2	16	EPDM	PGV-131-B76-6/4PP	614243	o. r.
		40	29.5	G 1 1/2	16	FKM	PGV-131-B76-6/4FP	614245	o. r.
		50	35	G 2	16	NBR	PGV-131-B76-2BP	614251	o. r.
		50	35	G 2	16	EPDM	PGV-131-B76-2PP	614253	o. r.
		50	35	G 2	16	FKM	PGV-131-B76-2FP	614255	o. r.

Version and function: 2/2-way solenoid valve Type PGV series 100 pressure operated by external medium, double-sided blocking


Remotely operated 2/2-way valve regulated by external medium with 3/2-way valve (positive control)




Remotely operated 2/2-way valve regulated by external medium with 2/2-way valve



Remotely operated pressure valve regulated by external medium with pressure regulator




2/2-Way Solenoid Valve - Type PGV Series 100 Pressure Operated by own Medium


Price group	53	Function "B" normally open (without control pressure)	low noise and impact-free closing, for neutral, gaseous and fluids	Brass					
Version	Control pressure [bar]	DN	Kv-value water [m³/h]	G	PN	Sealing material	Type	Order number	Price
2/2-way valve pressure operated, by own medium Permitted operating pressure 0.2 to 16 bar 	≥ operating pressure max. 16	15	5.6	G 1/2	16	NBR	PGV-131-B76-1/2BN	614301	o. r.
		15	5.6	G 1/2	16	EPDM	PGV-131-B76-1/2PN	614303	o. r.
		15	5.6	G 1/2	16	FKM	PGV-131-B76-1/2FN	614305	o. r.
		20	7.6	G 3/4	16	NBR	PGV-131-B76-3/4BN	614311	o. r.
		20	7.6	G 3/4	16	EPDM	PGV-131-B76-3/4PN	614313	o. r.
		20	7.6	G 3/4	16	FKM	PGV-131-B76-3/4FN	614315	o. r.
		25	16.8	G 1	16	NBR	PGV-131-B76-1BN	614321	o. r.
		25	16.8	G 1	16	EPDM	PGV-131-B76-1PN	614323	o. r.
		25	16.8	G 1	16	FKM	PGV-131-B76-1FN	614325	o. r.
		32	21	G 1 1/4	16	NBR	PGV-131-B76-5/4BN	614331	o. r.
		32	21	G 1 1/4	16	EPDM	PGV-131-B76-5/4PN	614333	o. r.
		32	21	G 1 1/4	16	FKM	PGV-131-B76-5/4FN	614335	o. r.
		40	29.5	G 1 1/2	16	NBR	PGV-131-B76-6/4BN	614341	o. r.
		40	29.5	G 1 1/2	16	EPDM	PGV-131-B76-6/4PN	614343	o. r.
		40	29.5	G 1 1/2	16	FKM	PGV-131-B76-6/4FN	614345	o. r.
		50	35	G 2	16	NBR	PGV-131-B76-2BN	614351	o. r.
		50	35	G 2	16	EPDM	PGV-131-B76-2PN	614353	o. r.
		50	35	G 2	16	FKM	PGV-131-B76-2FN	614354	o. r.

Version and function: 2/2-way solenoid valve Type PGV series 100 pressure operated by own medium

Remotely operated 2/2-way valve regulated by own medium with 2/2-way valve (negative control)



Remotely operated 2/2-way valve regulated by own medium with 2/2-way valve (control medium recycled)



Remotely operated pressure regulator valve regulated by own medium with pressure regulator (control medium recycled)

