



## DESCRIPTION

Visual level indicator

## MATERIALS

Transparent part: Trogamid T

Anti-shock protection: Painted steel

Fixing bolts: Zinc plated steel

Seals: NBR Nitrile (FKM Fluoroelastomer on request)

Double scale thermometer (Celsius and Fahrenheit)  
option available.

Tightening torque for the fixing bolts 10 Nm.

## PRESSURE

Max pressure 100 kPa (1 bar)


## WORKING TEMPERATURE

From -20°C to +90°C

## COMPATIBILITY

Full with fluids HH-HL-HM-HV-HTG (according to ISO 6743/4).  
For fluids different than the above mentioned, please contact  
our Customer Service.

## HYDRAULIC DIAGRAM



Is this datasheet the latest release? Please check on our website.



### ORDERING AND OPTION CHART

C	L	A	COMPLETE FILTER FAMILY		
			SIZE & LENGTH		
			11	12	13
		M	CONNECTION TYPE		
		M = metric thread	M	M	M
			CONNECTION SIZE		
		10 = M10	10	10	10
		12 = M12	12	12	12
		N	SEALS		
		N = NBR Nitrile	N	N	N
		F = FKM Fluoroelastomer	F	F	F
			ACCESSORIES		
		W = without	W	W	W
		T = with thermometer	T	T	T

### DIMENSIONS

	H1	H2	H3	D
CLA11M10NW	108	76	32	M10
CLA11M10NT	108	76	32	M10
CLA12M12NW	160	127	78	M12
CLA12M12NT	160	127	78	M12
CLA13M12NW	286	254	202	M12
CLA13M12NT	286	254	202	M12

