

Needle restrictor, free reverse flow Common cavity, Size 10

STVU-10A

04.01.05 - X - 85.00

RE 18321-11

Edition: 03.2016

Replaces: 01.2010



Description

With flow from 2 to 1, the valve provides a fully adjustable orifice restriction. Free flow is permitted from 1 to 2, regardless of valve adjustment, by when pressure overcomes the spring bias of the valve's check function.





Technical data

Max. operating pressure	350 bar (5000 psi)
Max. flow	80 l/min. (22 gpm)
Max. internal leakage ¹⁾	15 drops/min. closed
Fluid temperature range	-30 to 100 °C (-22 to 212 °F)
Installation torque	41 - 47 Nm (30 - 35 ft-lbs)
Weight	0.2 kg (0.44 lbs)
Cavity	CA-10A-2N (see data sheet 18325-70)
Lines bodies and standard assemblies	Please refer to section "Hydraulic integrated circuit" or consult factory
Seal kit ²⁾	Code: RG10A2010520100 material no: R901111363
Fluids	Mineral-based or synthetics with lubricating properties at viscosities of 5 to 800 mm ² /s (cSt)
Recommended degree of fluid contamination	Nominal value max. 10µm (NAS 8) / ISO 4406 19/17/14
Installation	No restrictions
Other Technical Data	See data sheet 18350-50

1) Measured at 200 bar (2900 psi)

2) Only external seals for 10 valves

Characteristic curve



Ordering code

04.01.05	X	85	00	00	*
----------	---	----	----	----	---

Series 0/A to L
unchanged performances and dimensions

Needle restrictor, free reverse flow

Version and options standard

Adjustments

03 Leakproof hex. socket screw

04 Handknob and locknut

85 Common cavity, Size 10

Preferred types

Type	Material number
040105038500000	R930005606
040105048500000	R930005607

Type	Material number

Dimensions

