

DRF Series - Medium - Economy type

- Outer hose : PU/PVC - Inner : PU polyester base



Technical characteristics

Technology: Pipe locked with ratchet stop

Max operating pressure: 12 bar

Construction: Epoxy-coated steel case


Connection: 1 m of inlet supply hose

180° swiveling bracket

Inlet : 1 m hose

Pressure : 12 bar

Temperature : -15°C to +65°C



A (mm)	B (mm)	ID/OD (mm)	Length (m)	Coupler	Fixed inlet (mm)	Flow rate (l/min)	Weight (kg)	Parts Numbers
340	302	8 x 12	12	BSI 06	8 x 12	500	6	DRF 0812BS
340	337	8 x 12	15	BSI 06	8 x 12	350	7	DRF 0815BS
340	302	10 x 14	10	BSI 06	10 x 14	750	5.7	DRF 1010BS
370	337	10 x 14	12	BSI 06	10 x 14	800	6.8	DRF 1012BS
370	337	10 x 14	15	BSI 06	10 x 14	800	7.2	DRF 1015BS
340	302	8 x 12	12	ESI 07	8 x 12	500	6	DRF 0812ES
370	337	8 x 12	15	ESI 07	8 x 12	350	7	DRF 0815ES
340	302	10 x 14	10	ESI 07	10 x 14	900	5.7	DRF 1010ES
370	337	10 x 14	12	ESI 07	10 x 14	800	6.8	DRF 1012ES
370	337	10 x 14	15	ESI 07	10x14	800	7.2	DRF 1015ES
340	302	8 x 12	12	ISI 06	8 x 12	500	6	DRF 0812IS
370	337	8 x 12	15	ISI 06	8 x 12	350	7	DRF 0815IS
340	302	10 x 14	10	ISI 06	10 x 14	833	5.7	DRF 1010IS
370	337	10 x 14	12	ISI 06	10 x 14	800	6.8	DRF 1012IS
370	337	10 x 14	15	ISI 06	10x14	800	7.2	DRF 1015IS
340	302	8 x 12	12	CSI 06	8 x 12	500	6	DRF 0812CS
370	337	8 x 12	15	CSI 06	8 X 12	350	7	DRF 0815CS
340	302	10 x 14	10	CSI 06	10 x 14	833	5.7	DRF 1010CS



Enclosed hose reels for compressed air / Steel

A (mm)	B (mm)	ID/OD (mm)	Length (m)	Coupler	Fixed inlet (mm)	Flow rate (l/min)	Weight (kg)	Parts Numbers
370	337	10 x 14	12	CSI 06	10 x 14	800	6.8	DRF 1012CS