

SR/CCK

The SR/CCK is specifically designed for the proportional quarter-turn operation for the actuation of butterfly, plug, ball valves, etc. It can be also used on linear actuators using a specific bracket. It is usually located in the control circuit between the air filter regulator and the actuator of the final control element. This positioner has a heavy duty design to make it suitable for use as part of the pneumatic valve set in the potentially harsh conditions found in petroleum, chemical, power, metal production and other hazardous fields.

This is a double acting positioner which can also be used as single acting. The SR/CCK positioner is equipped with a different linear cam (angle up to 270°) to allow use on actuators with different strokes.

Cam operating angles and range adjustments are printed on the positioner. Special cam profiles are available on request. This positioner is based on the balanced-forces principle and air distribution to the actuator chamber is executed by a spool.



Heavy duty design

Key features and benefits

- > Metallic case
- > Heavy duty design
- > High reliability
- > Split range signal
- > Special characterisation/range
- > Available with full stainless steel spool valve
- > Visual position indicator
- > Suitable for:
 - Standard, offshore, sandstorm, copper free ambient condition
 - Single and double acting actuators
 - Low and high ambient temperature



SR/CCK pneumatic version

Accessories

- > Pressure gauges

Technical specifications

外壳材料

铝漆黑色RAL 9005盖聚碳酸酯

CV 最大值

ND 1/4" Inlet = 0.34

ND 1/4" Outlet = 0.34

操作压力

P min = 2.5 bar

P max = 7 bar

Design pressure = 10 bar

工作温度

-20°C / +70°C

信号

3-15 psi

静态空气消耗量

1.02 Nm³/h (0.6 SCFM) at 400 kPa (60 psi)

灵敏度

0.25% of full range

供电连接

ND 1/4"

线性

1% of the full range with linear cam

输出连接

ND 1/8"

滞后

0.5% of the full stroke

导频信号连接

1/8" NPTF

重量

ND 1/4" = 0.9 kg

Dimensional drawing

