


Tank-Mounted Filter

ZT



Features and Benefits

- Low pressure tank-mounted filter
- Available with dual inlet porting
- Offered in pipe, SAE straight thread and ISO 228 porting
- Various Dirt Alarm® options
- Optional PAB1 breather
- Available with quality-protected GeoSeal® Elements (GZT)
- G** Same day shipment model available

 Part of the Schroeder Industries 2030 Initiative

40 gpm
150 L/min
100 psi
7 bar

Model No. of filter in photograph is ZT8ZZ10PPESAB.

Flow Rating:	Up to 40 gpm (150 L/min) for 150 SUS (32 cSt) fluids
Max. Operating Pressure:	100 psi (7 bar)
Min. Yield Pressure:	300 psi (21 bar), per NFPA T2.6.1
Rated Fatigue Pressure:	90 psi (6 bar), per NFPA T2.6.1-R1-2005
Temp. Range:	-20°F to 225°F (-29°C to 107°C)
Bypass Setting:	Cracking: 25 psi (1.7 bar) Full Flow: 39 psi (2.7 bar)
Cap & Bowl:	Nylon
Porting Head:	Aluminum
Weight of ZT-8Z:	3.3 lbs. (1.49 kg)
Element Change Clearance:	10.0" (254 mm)

Filter Housing Specifications

Type Fluid	Appropriate Schroeder Media
Petroleum Based Fluids	All E media (cellulose) and Z-Media® (synthetic)
High Water Content	All Z-Media (synthetic)
Invert Emulsions	10 and 25 µ Z-Media® (synthetic)
Water Glycols	3, 5, 10 and 25 µ Z-Media® (synthetic)
Phosphate Esters	All Z-Media® (synthetic) with H (EPR) seal designation

Fluid Compatibility

**Accessories
For Tank-
Mounted
Filters**

IRF

TF1

KF3

KL3

LF1

MLF1

RLD

GRTB

MTA

MTB

ZT

KFT

RT

RTI

LRT

ART

BRT

TRT

BFT

QT

KTK


LTK

MRT

PAF1

MAF1

MF2



Metric dimensions in ().

Element Performance Information & Dirt Holding Capacity

Element	Filtration Ratio Per ISO 4572/NFPA T3.10.8.8 Using automated particle counter (APC) calibrated per ISO 4402			Filtration Ratio wrt ISO 16889 Using APC calibrated per ISO 11171	
	$\beta_x \geq 75$	$\beta_x \geq 100$	$\beta_x \geq 200$	$\beta_x(c) \geq 200$	$\beta_x(c) \geq 1000$
8Z3	6.8	7.5	10.0	N/A	N/A
8Z10	15.5	16.2	18.0	N/A	N/A
8ZZ1	<1.0	<1.0	<1.0	<4.0	4.2
8ZZ3	<1.0	<1.0	<2.0	<4.0	4.8
8ZZ5	2.5	3.0	4.0	4.8	6.3
8ZZ10	7.4	8.2	10.0	8.0	10.0
8ZZ25	18.0	20.0	22.5	19.0	24.0

Element	DHC (gm)
8Z3	39
8Z10	32
8ZZ1	51
8ZZ3	52
8ZZ5	59
8ZZ10	55
8ZZ25	77


Element Collapse Rating: 150 psid (10 bar)

Flow Direction: Outside In

Element Nominal Dimensions: 3.2" (81 mm) O.D. x 9.25" (235 mm) long

$\Delta P_{\text{housing}}$


ZT $\Delta P_{\text{housing}}$ for fluids with sp gr (specific gravity) = 0.86:



$\Delta P_{\text{element}}$

8ZZ

Element Pressure Drop versus Flow Rate at 32 cSt (150 SUS)



$$\Delta P_{\text{filter}} = \Delta P_{\text{housing}} + (\Delta P_{\text{element}} * V_f)$$

Exercise:

Determine ΔP_{filter} at 30 gpm (119.7 L/min) for ZT8ZZ10SY2 using 160 SUS (34 cSt) fluid.

Use the housing pressure curve to determine $\Delta P_{\text{housing}}$ at 30 gpm. In this case, $\Delta P_{\text{housing}}$ is 3.5 psi (.24 bar) on the graph for the ZT housing.

Use the element pressure curve to determine $\Delta P_{\text{element}}$ at 30 gpm. In this case, $\Delta P_{\text{element}}$ is 3.5 psi (.24 bar) according to the graph for the 8ZZ10 element.

Because the viscosity in this sample is 160 SUS (34 cSt), we determine the **Viscosity Factor (V_f)** by dividing the **Operating Fluid Viscosity** with the **Standard Viscosity** of 150 SUS (32 cSt). To best determine your Operating Fluid Viscosity, please reference the chart in Appendix D.

Finally, the overall filter pressure differential, ΔP_{filter} , is calculated by adding $\Delta P_{\text{housing}}$ with the true element pressure differential, ($\Delta P_{\text{element}} * V_f$). The $\Delta P_{\text{element}}$ from the graph has to be multiplied by the viscosity factor to get the true pressure differential across the element.

Solution:

$$\Delta P_{\text{housing}} = 3.5 \text{ psi } [.24 \text{ bar}] \mid \Delta P_{\text{element}} = 3.5 \text{ psi } [.24 \text{ bar}]$$

$$V_f = 160 \text{ SUS (34 cSt)} / 150 \text{ SUS (32 cSt)} = 1.1$$

$$\Delta P_{\text{filter}} = 3.5 \text{ psi} + (3.5 \text{ psi} * 1.1) = 7.4 \text{ psi}$$

OR

$$\Delta P_{\text{filter}} = .24 \text{ bar} + (.24 \text{ bar} * 1.1) = .50 \text{ bar}$$

Pressure Drop Information Based on Flow Rate and Viscosity

Note:
If your element is not graphed, use the following equation:
 $\Delta P_{\text{element}} = \text{Flow Rate} \times \Delta P_f$. Plug this variable into the overall pressure drop equation.

Ele.	ΔP
8Z3	0.25
8Z10	0.09
8Z25	0.02

Filter
Model
Number
SelectionHighlighted
product eligible for
QuickDelivery

How to Build a Valid Model Number for a Schroeder ZT:

BOX 1	BOX 2	BOX 3	BOX 4	BOX 5	BOX 6	BOX 7	BOX 8
ZT							

Example: NOTE: One option per box

BOX 1	BOX 2	BOX 3	BOX 4	BOX 5	BOX 6	BOX 7	BOX 8
ZT	8	Z10		S	Y2		

= ZT8Z10SY2

BOX 1	BOX 2	BOX 3	BOX 4
Filter Series	Element Length (in)	Element Size and Media	Seal Material
ZT	8	Z3 = Z size 3 μ E media (cellulose) Z10 = Z size 10 μ E media (cellulose) Z25 = Z size 25 μ E media (cellulose) ZZ1 = Z size 1 μ Excellement® Z-Media® (synthetic) ZZ3 = Z size 3 μ Excellement® Z-Media® (synthetic) ZZ5 = Z size 5 μ Excellement® Z-Media® (synthetic) ZZ10 = Z size 10 μ Excellement® Z-Media® (synthetic) ZZ25 = Z size 25 μ Excellement® Z-Media® (synthetic) GeoSeal® Element Options GZ3 = Z size 3 μ E media (cellulose) GZ10 = Z size 10 μ E media (cellulose) GZ25 = Z size 25 μ E media (cellulose) GTZZ1 = Z size 1 μ Excellement® Z-Media® (synthetic) GTZZ3 = Z size 3 μ Excellement® Z-Media® (synthetic) GTZZ5 = Z size 5 μ Excellement® Z-Media® (synthetic) GTZZ10 = Z size 10 μ Excellement® Z-Media® (synthetic) GTZZ25 = Z size 25 μ Excellement® Z-Media® (synthetic)	Omit = Buna N H = EPR
BOX 5	BOX 6	BOX 7	BOX 8
Inlet Porting	Dirt Alarm® Options	Outlet Porting Options	Options
P = 1" NPTF PP = Dual 1" NPTF S = SAE-16 SS = Dual SAE-16 B = ISO 228 G-1" BB = Dual ISO 228 G-1"	Omit = None Visual Y2 = Back-mounted tri-color gauge Y2C = Bottom-mounted gauge in cap Y5 = Back-mounted gauge in cap Electrical ES = Electric switch ES1 = Heavy-duty electric switch with conduit connection	Omit = 1½" NPT male D = Diffuser T = 13" Tube extension	Omit = None G3039 = 1.5" NPT Outlet Removed B = Breather D = Diffuser M = Mounting Gasket (Buna N)