



**B.N.C.TOOLING Co.,Ltd.**

BNCTOOLING.COM  
BNCTOOLINGSHOP.COM



HELIOS • PREISSER

## 1866 Digital micrometers IP65



1866 410



1866 510



### Model

- Reading: 0.001 mm / .00005 inch
- Protection class IP65
- LCD display: 10 mm
- Rapid drive
- Carbide measuring faces
- Spindle stainless, hardened and smoothed
- Frame lacquered
- Thermally insulated
- Factory standard



### Functions


- ON / OFF
- Quick-Stat
- Quick-Lock (key lock)
- Set to zero at any point mm / inch switching
- ABS (display can be set to zero without losing the ORIGIN)
- Hold

- Additionally 1866 5xx:
- ORIGIN (Preset value)
- Variable data output
- USB + Digimatic
- TOL (tolerance value input)

### Delivery

- Plastic case
- From measuring range 25 mm upwards includes a setting standard

		Measuring range		Pitch mm	Spindle dia. mm	Error limit mm	Order no.
		mm	inch				
Without data output							
		0 - 25	0 - 1	0.5	6.5	0.002	1866 410
		25 - 50	1 - 2	0.5	6.5	0.002	1866 413
		50 - 75	2 - 3	0.5	6.5	0.003	1866 417
		75 - 100	3 - 4	0.5	6.5	0.003	1866 420
With DataVariable bidirectional							
		0 - 25	0 - 1	0.5	6.5	0.002	1866 510
		25 - 50	1 - 2	0.5	6.5	0.002	1866 513
		50 - 75	2 - 3	0.5	6.5	0.003	1866 517
		75 - 100	3 - 4	0.5	6.5	0.003	1866 520



1998725

1998802

### Accessories

	Order no.
Battery, 3V-Lithium, CR 2032	0220 704
Data cable bidirectional DataVariable to USB	1998 801
Data cable bidirectional DataVariable to Digimatic	1998 802

Marked • = excess length/excess weight

Marked • = includes a F.O.C. calibration certificate, traceable to national standards