



Product name

2-jaw puller

For removing bearings, gears, discs, etc.

Art. No. 20-4

Series 20

EAN 4021176009761

	Technical attribute	Metric	Imperial
	Spread	80 - 520 mm	3 3/16 - 20 1/2 inch
	Depth	200 mm	7 7/8 inch
	Spread used internal	200 - 590 mm	7 7/8 - 23 3/8 inch
	Hexagon drive (male)	36 mm	
	Maximum torque	400 Nm	295 ft lb
	Maximum load	12,0 t	1 US t
	Weight	14 kg	
	Number of jaws	2	2
	Space below	20 mm	3/4 inch
	Space next to it	67 mm	2 5/8 inch




Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
633400	Mechanical pressure spindle.
3-200-P	2 pulling jaws (pair)
20-4-T	2-jaw cross bar

Accessories

Art. No.	Product name
8-1-B	Long hydraulic spindle
9-1	Auxiliary hydraulic ram
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
3-300-P	2 extended jaws (pair)
3-400-P	2 extended jaws (pair)
3-500-P	2 extended jaws (pair)
3-200-E	Jaws (individual)
3-250-P	2 pulling jaws (pair)
8-HP-100	Long hydraulic spindles with handle



Can be used alternatively with

Art. No.	Product name
3-201-P	2 narrow jaws (pair)
3-301-P	2 narrow jaws (pair)
3-401-P	2 narrow jaws (pair)
3-501-P	2 narrow jaws (pair)
3-202-P	2 quick adjusting jaws (pair)
3-302-P	2 quick adjusting jaws (pair)
3-402-P	2 quick adjusting jaws (pair)
3-502-P	2 quick adjusting jaws (pair)
3-203-P	2 narrow, quick adjusting jaws (pair)
3-303-P	2 narrow, quick adjusting jaws (pair)
3-403-P	2 narrow, quick adjusting jaws (pair)
3-503-P	2 narrow, quick adjusting jaws (pair)

