

3-393-R001 / R002

SF₆ gas refilling device

For reliable refilling of SF₆ gas by overpressure

3-393-R001

SF₆ gas refilling device

Portable with rubber hose and couplings DN8 and DN20

3-393-R002

SF₆ gas refilling device

Portable **in a case** with rubber hose and couplings DN8 and DN20

The handy devices allow filling of electrical equipment with SF₆ gas directly from the bottle by overpressure. The primary gauge of the pressure reducer displays the bottle pressure in bar, the secondary gauge indicates the desired filling pressure to be set easily by means of the handle. The bottle pressure can be reduced to the desired filling pressure by the integrated pressure reducer.



- Self-closing couplings for emission-free gas handling
- Available as accessories for the world's most commonly used bottle connections

3-393-R001 / 3-393-R002

SF₆ gas refilling device

Technical data:

Case dimensions: L 500 mm, W 420 mm, H 180 mm
Weight: 7.5 kg

Standard equipment for both versions:

Pressure reducer for SF ₆ gas with W 21.8 x 1/14" thread
5 m long hose DN8
DILLO coupling tongue parts DN8 and DN20
Gauge indication in bar
2 operating manuals in 3 languages (German / English / French)

Optional accessories at an extra charge:

SF ₆ bottle connection with 0.96" Whitworth left-handed thread	3-245-R001 P
English SF ₆ bottle connection with G 5/8 thread	3-245-R002 P
SF ₆ bottle connection with G 5/8 thread	3-643-R001 P
Additional operating manual on CD-ROM	6-0004-R213

Packing:

Packing for 3-393-R001	3-948-R006
Packing for 3-393-R002	05-1990-R003

Note:

Other versions are available on request.