


Technical data:


Max.operating pressure	350 bar
Max.flow	240 l/min
Max.internal leakage	4 cm ³ /min (*)
Fluid temperature range	-30/+100 °C
Installation torque	208-234 Nm
Weight	1.00 kg
Cavity	003 (special)
Seal kit	RG0003020520100 (**) R930001695
Fluids	Mineral based or synthetics with lubricating properties at viscosities of 10 to 500 mm ² /s (cSt)
Filtration	Nominal value max. 10 µm (NAS 8) ISO 4406 19/17/14

(*) At 80% of pressure setting

(**) Only external seals for ten valves



Z	Springs		
	Adj.press. range bar	Press.increase bar/turn	Standard setting (bar) Q=5 l/min
10	35-100	18	100
20	70-210	36	200
35	120-350	62	350

Denominazione / Denomination		Rexroth Bosch Group Bosch Rexroth Oil Control S.p.A.	
VSD-250			
Specifiche Specifications	-	Ufficio Tecnico Technical Dep. DC-MA/ECC1	
	-	Gerarchia Prodotto Product Hierarchy 871117601	
	-	Kit guarniz. Seal kit RG0003020520100	
	-	Modifiche Changes	
Massa / Mass (kg) -		Cliente e codice articolo Customer and article code -	
Richiesta / Request UT11950		Num. schema idraulico / Hydraulic scheme no. bs_0010	
Tipo cavità Cavity type 003		Studio di riferimento / Reference study -	
 A3		Sostituiscie il Replaces -	
Disegno di proprietà BOSCHREXROTH OIL CONTROL S.p.A. tutelato ai termini di legge. E' vietata la riproduzione e la diffusione non autorizzata. This drawing is a property of BOSCHREXROTH OIL CONTROL S.p.A. protected according to the laws. Unauthorized reproduction and distribution is strictly prohibited.		Disegnato / Designed by Moretti Data / Date 20/12/12	
		Verificato / Checked by Tagliazucchi Scala / Scale 1:1	
		Codice Code 0415039299Z	
		Direttorio del file Cad / Cad file directory K:\Design\Cad 3D\Ingombri\0415039299Z\	
		Material number	