

MOLYDUVAL

Cicli Chain



Chain Fluid for Bicycles

Properties

- * compatible with mineral oil
- * relative good compatible with elastomers and seals
- * wide temperature range
- * good viscosity atability even under high shear rates
- * good oxidation resistance
- * high flash point
- * protects from wear

Applications

- * for bicycle chains

Technical Datas

Base Fluid		Ester
Viscosity Class	ISO-VG	150
Density 15°C	kg/m ³	910
Viscosity 40°C	mm ² /s	150
Flash Point	°C	270
Viscosity Index		174
Pour point	°C	-30
Wear Protection FZG test	Grade	12
Wear Protection VKA welding load	N	1400

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.